Product data sheet

Reversible plate compactor CR 6 Hd ltem No. 000116538



| | | 000 | 110000 | | | | |
|---|-------------|-------------------------------|--|--------------------------|-----------------|----------------|--|
| Dimensions | | | | | | | |
| service weight CECE (standard | d) | 360 [kg] | | L ₂ | | | |
| weight without extension plates | | [kg] | | | | | |
| weight with small extension plates | | 360 [kg] | | | | | |
| weight with large extension plates | | 373 [kg] | | | | | |
| working width | (W) | 590 [mm] | | | | | |
| width without extension plates | (W1) | 450 [mm] | | | 1 | H ₂ | |
| with small extension plates | (W2) | 590 [mm] | | £ Panno | | Ŧ | |
| with large extension plates | (W3) | 740 [mm] | | | | | |
| overall lenght | (L1) | 1710 [mm] | ************************************** | | | | |
| overall height | (H1) | 1160 [mm] | W ₁ | L ₄ | | | |
| shipping dimension lenght | (L2) | 980 [mm] | W2/W3 | L ₃ | | 50 ()) | |
| shipping dimension height | (H2) | 1370 [mm] | | _ | L ₁ | CR 6 Hd | |
| lenght | (L3) | 980 [mm] | conta | ct lenght of base pla | ite (L4) 45 | 0 [mm] | |
| Performance | | | | Control displays | | | |
| centrifugal force | | 55 [kN] | | air filter | | | |
| exiter frequency | | 72 [Hz] | | oil pressure | | | |
| working speed | | 0-27 [m/min] | | batterie capacity | | | |
| yardage | | 955 [m²/h] | |] maintanance servic | e | | |
| gradability | | 35 [%] | V | hour meter standar | d | | |
| PQ categorie | | PQ 4 | | | | | |
| Engine data | | | | | | | |
| engine manufacturer | Hono | da | type o | of combustion | 4-stroke petrol | | |
| type of engine | GX 390 | | type o | of starter | Manual start | | |
| performance (ISO 3046-1) | | 8,7 [kW] | fuel o | onsumption. (80% lo | oad 2,5 [L] | | |
| output at service r.p.m. | | 6,4 [kW] | fuel to | ank capacity | 6,0 [L] | | |
| service r.p.m. of engine 2750 [1/min] | | 4 2 112 2 | of vibration | \/ b a l t | | | |
| automatic switch off | ✓ | | туре с | of vibration | V-belt | | |
| Emission | | | | | | | |
| sound power level Lwa | 108 [dB(A)] | | EU e | mission certificate | EU Stage V | | |
| hand-arm vibration 2,4 [m/s²] | | US emission certificate EPA 3 | | | | | |
| Accessories | | | | | | | |
| wheel kit [Item No.] | | | | watertank L [| Item No | | |
| hour meter [Item No.] Serie | | | | irrigation tube [Item No | | | |

hour meter [Item No.] Serie irrigation tube [Item No. --- service kit [Item No.] 041001423

590 [mm] polyurethane pad [Item No.] 000195663

590 [mm] polyurethane pad [Item No.] extension plates, pair [Item No. Serie

740 [mm] polyurethane pad [Item No.] 000195664 extension plates, pair [Item No. 000196673